

Slim Line Series Cardioid Microphones with Mini XLR Connector designed for use in boardrooms, conferencing and a wide variety of applications requiring easily detachable gooseneck microphones with good consistent sound quality.



- Semi Rigid goosenecks or Rigid shaft
- Slimline unobtrusive design
- Engineered in high quality brass
- Mini XLR connector for easy interchange
- Cardioid condenser microphone
- C3 series wideband quality
- Easy connection to SM20-RF, SM80-RF and SM80S-RF shock mounts, PPA-RF, S140-RF or CW9004 wireless microphone base
- Finished in satin black

## SPECIFICATIONS

<b>Type:</b>	Condenser (black electret)
<b>Polar Pattern:</b>	Cardioid
<b>Frequency Response:</b>	50 Hz - 18 KHz
<b>Sensitivity:</b>	-47dB +/- 3dB @ 1 KHz (0dB = 1 V/Pa)
<b>Impedance:</b>	200 Ohms
<b>S/N Ratio:</b>	64dB(A)
<b>Maximum SPL:</b>	125dB 1% THD
<b>Power Requirements:</b>	PPA-RF, SM20-RF, SM80-RF, SM80S-RF, S140-RF, CW9004
<b>Termination:</b>	3 pin female Mini XLR connector. Pin 1 Phase - Pin 2 Phase + Pin 3 not used.
<b>Accessories:</b>	W2 Windshield included
<b>Dimensions:</b>	
<b>Head Diameter:</b>	0.5" (12mm)
<b>Shaft Diameter:</b>	0.2" (6mm)
<b>Overall Length:</b>	C 312-SR 7.85" (200mm) C 313-SR 11.8" (300mm) C 314-SR 15.75" (400mm)
<b>Net Weight:</b>	.2oz (29gms)
<b>Finish:</b>	Satin Black

